



15" Small Footprint All-in-One touch POS PC

Features

- Second displays support including digital signage, monitor and VFD display.
- Full I/O interface for peripherals
- Smart mechanical design
- Dust-proof CPU Protection
- Heat-dissipated Aluminum Chassis
- IP-64 Compliant Front Panel

Specifications

Model Name	EP-165N270
LCD	15"
CPU	Intel® Celeron®
Memory	1GB
Storage	160GB
OS	Windows 7
Interface	Intel® Core™ Duo

M 1 GHz 512KB L2 Cache
Intel® Core™ N270
1.6GHz

Chipset Intel® Core™ N270

- I/O Interface 1 x VGA
- 5 x Powered COM (5V/12V/RI)
 - 7 x PoweredUSB (5V/12V/24V)
 - 2 x RJ-12 Digital I/O for Cash Drawer
 - 1 x DB-25
 - 1 x 12V/ 24V DC Output
 - 1 x Power Switch
 - 1 x AT/ATX Power Mode
 - 5 x Powered COM (5V/12V/RI)
 - 7 x PoweredUSB (5V/12V/24V)
 - 2 x RJ-12 Digital I/O for Cash Drawer
 - 1 x DB-25
 - 1 x 12V/ 24V DC Output
 - 1 x Power Switch
 - 1 x AT/ATX Power Mode
 - 5 x Powered COM (5V/12V/RI)
 - 7 x PoweredUSB (5V/12V/24V)
 - 2 x RJ-12 Digital I/O for Cash Drawer
 - 1 x DB-25
 - 1 x 12V/ 24V DC Output
 - 1 x Power Switch
 - 1 x AT/ATX Power Mode
 - 5 x Powered COM (5V/12V/RI)
 - 7 x PoweredUSB (5V/12V/24V)
 - 2 x RJ-12 Digital I/O for Cash Drawer
 - 1 x DB-25
 - 1 x 12V/ 24V DC Output
 - 1 x Power Switch
 - 1 x AT/ATX Power Mode
 - 5 x Powered COM (5V/12V/RI)
 - 6 x PoweredUSB (5V/12V)
 - 1 x RJ-12 Digital I/O for Cash Drawer
 - 1 x DB-25
 - 1 x Power Switch
 - 1 x AT/ATX Power Mode

Memory Built-in 1GB DDR2

Max Resolution 1024x768x1024

Brightness (cd/m²)	350350250250250
Contrast Ratio	700700600600600:1
LCD Color	262K262K6.7M6.7M6.7M
Touch Screen Type	Resistive Type 5-Wire
Pixel Pitch (mm)	0.297(H) x 0.297(V)
Viewing Angle (H-V)	140/140125/125160/160
Backlight MTBF	500004000040000 hours
IP Level	IP64 (front panel)
Front Panel Color	Black
HDD	1 x 2.5" SATA HDD Bay
SSD	1 x CF Type II slot
Power Consumption	50W88W50W88W TDB
EMC and Safety	CE/ FCC/ CB/ UL
Operating Temperature	0°C~40°C
Dimension (WxHxD) (mm)	387 x 321 x 221
Net Weight	8.34Kg

Ordering Information	
Part No.	Description
EP-165-910-10G/WT-R/1GB	350cd/m² XGA POS PC with Intel® Celeron® M 1.0GHz 512K cache CPU
EP-165-945-CM440/WT-R/1GB	350cd/m² XGA POS PC with Celeron® M 440 1.8GHz CPU, 1GB DDR2
EP-165-945-T2300E/WT-R/1GB	350cd/m² XGA POS PC with Core™ Duo T2300E 1.66GHz CPU, 1GB D
EP-165-910E-10G/WT-R/1GB	250cd/m² XGA POS PC with Intel® Celeron® M 1.0GHz 512K cache CPU
EP-165E-945-T2300E/WT-R/1GB	250cd/m² XGA POS PC with Intel® Core™ Duo T2300E 1.66GHz CPU,
EP-165E-N270/T-R/1GB	250cd/m² XGA POS PC with Intel® Atom™ N270 1.6GHz, 1GB DDR2 F