



---

*15" 250cd/m<sup>2</sup> Economical all-in-one touch POS PC*

---

Features

- Fanless design for rigorous environments
- Customer-friendly self-service solutions
- All-in-one easily maintained system
- Versatile mounting suits diverse applications
- Selectable AT or ATX power mode
- Built-in 1.5 W speakers
- IP 64 front panel protection withstand harsh environment

Specifications

|     |                            |
|-----|----------------------------|
| LCD | 15" TFT LCD                |
| CPU | AMD Geode™ LX 800 (500MHz) |

|                                                        |                                                                   |
|--------------------------------------------------------|-------------------------------------------------------------------|
| Chipset                                                | AMD Geode™ LX 800+ AMD Geode™ CS5536                              |
| I/O Interface                                          | <del>USB</del> USB 2.0                                            |
| <b>Serial/COM</b>                                      | 2 x RS-232 COM Port (pin 9 with RI , 5V or 12V switch selectable) |
| With LED Indicator (12V--Red / 5V--Yellow / RI--Green) |                                                                   |
| <b>LAN (10/100Mbps)</b>                                | 1 x RJ-45                                                         |
| <b>Cash Drawer Port</b>                                | 1 x RJ-12 (12V) for Cash Drawer                                   |
| <b>DC Jack</b>                                         | 1 x DC Jack                                                       |
| 1 x Power Switch                                       |                                                                   |
| 1 x Reset Button                                       |                                                                   |
| <b>POWER LED</b>                                       | 1                                                                 |

|                     |                                                            |
|---------------------|------------------------------------------------------------|
| Memory              | Supports one 1GB (maximum)333MHz or 400MHz SO-DIMM         |
| Max Resolution      | 1024 x 768                                                 |
| Brightness (cd/m²)  | 250                                                        |
| Contrast Ratio      | 700:1                                                      |
| LCD Color           | 262K                                                       |
| Touch Screen Type   | Resistive Type 5-Wire                                      |
| Pixel Pitch (mm)    | 0.297(H) x 0.297(V)                                        |
| Viewing Angle (H-V) | 140(H) / 125(V)                                            |
| Backlight MTBF      | 50000 hrs                                                  |
| IP Level            | IP 64 in front                                             |
| Front Panel Color   | Silver                                                     |
| HDD                 | 1 x 2.5" HDD bay With ANTI-SHOCK                           |
| SSD                 | CF Type II                                                 |
| Mini-PCI Slot       | 1x mini-PCI slot (for build-in wireless 802.11 b/g module) |
| Built-in Speaker    | AMP 1.5W+AMP 1.5W                                          |
| Power Adapter       | P/N. No.: 63000-FSP0601AD101C-RS                           |

Power: 60W

Input: 90VAC~264VAC @ 50/60Hz

Output:12VDC

|                        |                                                                     |
|------------------------|---------------------------------------------------------------------|
| Power Consumption      | 38W                                                                 |
| MSR                    | Magnetic Card Reader (USB interface) (optional)                     |
| MSI                    | Magnetic Card, Smart Card,Dallas iButton (USB interface) (optional) |
| Cash Drawer            | RJ-12 (12VDC) interface (optional)                                  |
| Bar Code Reader        | Hand-held Laser Scanner (USB interface) (optional)                  |
| EMC and Safety         | CE, FCC, CCC, CB                                                    |
| Operating Temperature  | 0°C~50°C                                                            |
| Storage Temperature    | -20°C~60°C                                                          |
| Dimension (WxHxD) (mm) | 394 x 309 x 61                                                      |
| Mounting               | Panel, Wall, Stand VESA 100 x 100mm                                 |
| Net Weight             | 3.2 Kg                                                              |
| OS Support             | Windows XPE, Windows CE 5.0 or Windows CE 6.0 (optional)            |
| Watchdog Timer         | Software programmable supports 1~255 sec. System reset              |

Ordering Information

| Part No. | Description |
|----------|-------------|
|----------|-------------|

|                              |                                                               |
|------------------------------|---------------------------------------------------------------|
| AFL-15AE-LXPOS/WT-R/256MB/10 | 256MB/10" XGA fanless PPC with AMD Geode LX 800 CPU,256MB DDR |
|------------------------------|---------------------------------------------------------------|